RAYZER

LED MODULAR LIGHTING SYSTEM

Actual Size

RAYZER

LED MODULAR LIGHTING SYSTEM

THE LED ADVANTAGE

Applications

- Under and Over Cabinet Lighting
- Display Lighting
- Task Lighting
- Office Lighting
- Utility Areas
- Cove Lighting

Features

- Durable, Aluminum Low-Profile Design
- 50,000 Hour L70 Rated Life
- Warm Color Temperature with Even Illumination (3000K with CRI 85)
- Dimmable (using optional step dimmer)
- Mounting Clips for Flush or 30° Mounting Allow for Quick & Easy Installation
- Available in 9", 12" & 18"

LITHONIA LIGHTING®

An AcuityBrands Company

lighting facts

LED Product Partner

ENERGY STAR

RAYZER

LED MODULAR LIGHTING SYSTEM

3yr WARRANTY

Description		Dimensions	Model Number
Fixture	**Input Watts**		
9" RAYZER Linkable LED.....	5.3 watts	L= 9-1/4" W= 1-1/4" H= 1/2"	RAZ9
12" RAYZER Linkable LED.....	7.1 watts	L= 12-1/4" W= 1-1/4" H= 1/2"	RAZ12
18" RAYZER Linkable LED.....	10.6 watts	L= 18-1/4" W= 1-1/4" H= 1/2"	RAZ18
All Fixtures 34 Lumens/Watt (measured)			
Transformers			
RAYZER 24v Transformer- 120v power source		L= 5" W= 3" H= 1-3/8"	RAZTRANS24 120
RAYZER 24v Transformer- Multi-Volt power source		L= 5" W= 3" H= 1-3/8"	RAZTRANS24 MVOLT
Accessories			
RAYZER Step Dimmer		L= 2" W= 1-1/4" H= 1/2"	RAZDIM
RAYZER 24" Linking Cord (fixture to fixture)		L= 24"	RAZ CC24
RAYZER 3" Linking Cord (fixture to fixture)		L= 3"	RAZ CC3
RAYZER Low Voltage Linking Cord (cord to cord)		L= 3"	RAZ LVCC
RAYZER End Row Connector		L= 1-1/8"	RAZ ERC
RAYZER Power Hub Distributor		L= 1-1/2" W= 1-1/4" H= 1/2"	RAZ PHD
RAYZER In-Line Power Switch		L= 26"	RAZ INSL26

9"

12"

18"

Installation Diagram

Note: Fixture includes 18" linking cord, mounting clips for flush or 30° mounting, and screws.

Flush and 30° mounting clips are used with fixtures, power hub distributor and touch dimmer.

18" Linking Cord (included)
Use to link around corners or for wider spacing between fixtures
24" Linking Cord Available (optional)

Power Hub Distributor (optional)
Allows for versatile wiring



Plug In
Standard



6' power cord included with transformer

24 Volt Transformer (required, sold separately)
Includes 6' power cord for plug in installation and 24" linking cord to connect the transformer to the first stick

Link up to 10' of fixtures
(not including linking cords)

End Row Connector (optional)
Use connector to link fixtures



Step Dimmer (optional)

In-Line Power Switch (optional)
Connects the transformer to the linking cord

3" LED Linking Cord (optional)
Use to link fixtures around corners or for wider spacing between fixtures

Direct-Wire
Optional

Splice Box:
UCD JB (white)
UCD JB BL (black)

24" Connector Cord:
UC ERC24 R12 (white)
UC ERC24 BL R12 (black)

Splice Box and 24" Connector Cord (optional)
Required for direct-wire installation

c UL us LISTED

©2010 Acuity Brands Lighting, Inc. • One Lithonia Way, Conyers, GA 30012 • Phone: 888-557-4676 • www.lithonia.com